



pillar 1

ADVANTAGES

- Architectural stylish appearance
- Fully aluminium and glass
- Easy maintenance, anti corrosion
- Choice of color

APPLICATION



- Entrance, canopies, subway pedestrian, building
- Suggested mounting height : 4~6m

FEATURES

- Enclosed luminaire for ceiling mounting – downlighting.
- Die cast aluminium housing.
- Finished with epoxy powder paint. Standard Colour – Black.
- Ballast components mounted on a removable gear tray.
- Anodised finish on aluminium reflector – standard wide beam (others optional).
- Thermal shock resistant tempered glass.
- Ceramic lamp holder with silver plated contact – Standard G24d2.

CHARACTERISTICS

- Optical assembly : IP 65
- Ballast Compartment : IP 65
- Electrical Insulation : Class 1
- Voltage : 220V~240V
- Wattage : 18W~75W
- Lamp Type : PLC & M/H
(other lamp available upon request)
- Dimensions (mm) : ø151(L) x 228(H)
- Approx. Net weight : 4~6 kg



18W PLC



Model No.	Description	Voltage	Frequency	Lamp
GPKP1301	PILLAR 1 1X18W PLC C/W Control Gear & Lamp	220-240V	50-60Hz	G24d2
GPKP1302	PILLAR 1 1X26W PLC C/W Control Gear & Lamp	220-240V	50-60Hz	G24d3
GPKP1303	PILLAR 1 PAR30 75W Max. C/W Control Gear & Lamp	220-240V	50-60Hz	E27

ordering information