






pillar 2



dimension (mm)



70W MH



150W MH

ADVANTAGES

- Architectural stylish appearance
- Fully aluminium and glass
- Easy maintenance, anti corrosion
- Choice of color

APPLICATION

- Entrance, canopies, subway pedestrian, building
- Suggested mounting height : 4~6m

FEATURES

- Enclosed luminaire for ceiling mounting – downlighting.
- Die cast aluminium housing.
- Finished with epoxy powder paint. Standard Colour – Black.
- Ballast components mounted on a removable gear tray.
- Anodised finish on aluminium reflector – standard wide beam (others optional).
- Thermal shock resistant tempered glass.
- Ceramic lamp holder with silver plated contact – Standard G12.

CHARACTERISTICS

- Optical assembly : IP 65
- Ballast Compartment : IP 65
- Electrical Insulation : Class 1
- Voltage : 220V~240V
- Wattage : 35W~150W
- Lamp Type : PLC & M/H (other lamp available upon request)
- Dimensions (mm) : ø200(L) x 320(H)
- Approx. Net weight : 4~6 kg



Model No.	Description	Voltage	Frequency	Lamp
GPKP1401	PILLAR 2 1x35W MH C/W Control Gear & Lamp	220-240V	50-60Hz	G12
GPKP1402	PILLAR 2 1x70W MH C/W Control Gear & Lamp	220-240V	50-60Hz	G12
GPKP1403	PILLAR 2 1x150W MH C/W Control Gear & Lamp	220-240V	50-60Hz	G12
GPKP1404	PILLAR 2 1x35W CDM-R C/W Control Gear & Lamp	220-240V	50-60Hz	E27
GPKP1405	PILLAR 2 1x70W CDM-R C/W Control Gear & Lamp	220-240V	50-60Hz	E27

ordering information