





### pillar 3



PLC 18W



#### ADVANTAGES

- Architectural stylish appearance
- Easy maintenance, anti corrosion
- Choice of color

#### APPLICATION

- Building entrance, canopies, subway pedestrian
- Suggested mounting height : 4~6m

#### FEATURES

- Enclosed luminaire for wall mounting downlight.
- Die cast aluminium sheet.
- Finished with epoxy powder paint. Standard Colour – Black.
- Ballast components mounted on a removable gear tray.
- Anodised finish on aluminium reflector.
- Thermal shock resistant tempered glass.
- Ceramic lamp holder with silver plated contact – Standard G12.

#### CHARACTERISTICS

- Optical assembly : IP 65
- Ballast Compartment : IP 65
- Electrical Insulation : Class 1
- Voltage : 220V~240V 50/60 Hz
- Wattage : 18W~75W
- Lamp Type : M/H (other lamp available upon request)
- Dimensions (mm) :  $\phi 150(L) \times 310(H)$
- Approx. Net weight : 4~6 kg



Model No.	Description	Voltage	Frequency	Lamp
GPCP0273	PILLAR 3 PAR30 75W Max. C/W Lamp	220-240V	50-60Hz	E27
GPCP0275	PILLAR 3 1x18W PLC C/W Control Gear & Lamp	220-240V	50-60Hz	G24d3
GPCP0276	PILLAR 3 1x26W PLC C/W Control Gear & Lamp	220-240V	50-60Hz	G24d3

# ordering information