





rectangolo



ADVANTAGES

- Architectural stylish appearance

APPLICATION

- Walkway, corridor, alley
- Car park, staircase, building

FEATURES

- Enclosed luminaire for wall/ceiling.
- Die cast aluminium housing.
- Finished with epoxy polyester paint – White or Black.
- High impact resistant opal polycarbonate diffuser.
- Stainless steel locking devices.
- Weatherproof and durable silicon sealed rubber gasket.

CHARACTERISTICS

- Optical assembly : IP 54
- Ballast Compartment : IP 54
- Electrical Insulation : Class 1
- Voltage : 220V~240V 50/60 Hz
- Wattage : 13W~18W
- Lamp Type : 1 x PLC
: 2 x PLC
- Dimensions (mm) : 342(L) x 182(W) x 120(H)
- Lamp Holder : G24d1 (VDE)
G24d2 (VDE)
G24d3 (VDE)



| Model No. | Description | Voltage | Frequency | Lamp |
|-----------|--|----------|-----------|-------|
| GPCP0564 | RECTANGOLO 2x13W C/W Control Gear & Lamp | 220-240V | 50-60Hz | Gx24d |
| GPCP0551 | RECTANGOLO 2x18W C/W Control Gear & Lamp | 220-240V | 50-60Hz | Gx24d |
| GPCP0563 | RECTANGOLO 1x26W C/W Control Gear & Lamp | 220-240V | 50-60Hz | Gx24d |

ordering information