

Vienna 150W CDM-T

## vienna

### ADVANTAGES

- Architectural stylish appearance
- High performance, easy maintenance
- Anti corrosion

### APPLICATION


- Streets, pedestrian, parking area, security
- Perimeter, park, architectural & landscape
- Suggested mounting height : 3.5~5 meters

### FEATURES

- Enclosed luminaire for post top mounting.
- Die cast aluminium housing with cover.
- Finished with epoxy cationic electrocoating and phosphochromate treatment paint. Corrosion resistant.
- Standard colour – Black. Other colours available upon request.
- Ballast compartment mounted on a removable gear tray.
- Light pollution – indirect reflector.
- Adjustable spigot for 60~76mm diameter.
- Lamp holder in ceramic with silver plate contacts.
- Top reflector can be tilted on 30 deg. for asymmetrical light distribution.

### CHARACTERISTICS

- Optical assembly : IP 65
- Ballast Compartment : IP 65
- Electrical Insulation : Class 1
- Voltage : 220V~240V 50/60 Hz
- Wattage : 70~150W
- Lamp Type : CDM-T
- Dimensions (mm) : 997 x 580(H)
- Approx. Net weight : 12~15 kg



Model No.	Description	Voltage	Frequency	Lamp
GPCP330001	VIENNA 70W MH CDM-T C/W Control Gear & Lamp	220V-240V	50-60Hz	G12
GPCP330002	VIENNA 150W MH CDM-T C/W Control Gear & Lamp	220V-240V	50-60Hz	G12

# ordering information