




linear NIDA

The Nida is a new innovative range of compact modules luminaire, it is an LED tube batten fitting which offers comprehensive LED lighting, in terms of appearance and design of the light and compliance with all relevant safety requirements for operation.



- 1
 - 2
 - 3
 - 4
 - 5
 - 6
 - 7
- APPLICATION COLOR CODE

nida - - -

SOURCE	LED
LUMENS	300~1100
LAMPLIFE	50,000 HRS
INPUT VOLTAGE	85~265 VDC
OPERATING TEMP	-20°~40°
PROTECTION RATING	N.A.

COLOR CODE	COLOR	BEAM ANGLE	POWER (WATTS)	PROJECTION DISTANCE	HOUSING DESCRIPTION	GEAR/CONTROLS	SIZE (MM)	SCHEMATIC DIAGRAM
WARM	3000K	10° 30° 15X50° 6X40°	18W 30W	N.A.	ALUMINUM BODY	REMOTE DRIVER + DMX DECODER (DMX CONTROLLABLE)	LENGTH	see Appendix
COOL	5500K						500.0, 600.0, 1199.0, 1499.0	
ORED	RED						WIDTH	
OGRN	GREEN						26.0 Ø	
OBLU	BLUE						HEIGHT	
ORGB	RGB							

**The company is constantly developing and improving its products. All descriptions, illustrations, and specifications mentioned present only general particulars and shall not form any part of any contract. The right is reserved to change specifications without prior notice.

**FILL UP ORDERING REFERENCE ACCORDINGLY > example: NAME - - -